

ponsec



Marine & Yacht BUNKERING HOSE

Non-marking. Lloyds approved.

- Available in 3" and 4" sizes—any length.
- Features unique "through-the-weave" one piece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining.
- Manufactured in compliance with BS EN ISO 9001:2000 Quality Management Systems. Raw materials, components, and finished products are rigorously tested and inspected to ensure excellent product reliability.
- Approved to UK Water Byelaws Scheme BS 6920 as suitable for conveying cold and hot potable water up to 50°C.
- Polymer approved to USA Food & Drug Administration CFR 177.2600 for conveying food-stuffs.
- Approved by Lloyd's Register of Shipping.
- Available with a range of reusable fieldfittable high security couplings. Capable of accepting standard hose accessories including hooks, self-seal and breakaway couplings.

CONTACT:

Ponsec Rotary Equipment, S.L.
Edificio "El Far"
Paseo Juan de Borbón, 76
08039 Barcelona

Tel.: +34 93 224 70 13

Fax: +34 93 221 94 80

E-mail: ponsec@ponsec.net

A flexible layflat hose for all types of marine & yacht supply operations. Will not mark decks.

- **Orange (water)**

High visibility orange for potable water and food-stuffs,

- **Green (fuel)**

Green for diesel and other fluids.

- **Easy to Store & Transport**

Lightweight and compact for economical storage.

- **Fast Deployment & Retrieval**

Long continuous lengths can be quickly deployed and retrieved using light duty or power driven reels.

- **Low Operating Costs**

Low pressure loss for efficient pumping. Swells up to 15% above uncharged diameter at maximum operating pressure achieving higher flow rates and maximising cost savings.

- **High Performance Capability**

Designed for continuous operation at high working pressures and end tensile loads.

- **Long Service Life**

Capable of operating continuously at high pumping pressures with minimal maintenance in even the harshest environments. Tough and durable with exceptional resistance to abrasion and cutting for use in a variety of ground or sea conditions. Resistant to heat, fuels, chemicals, UV, ozone, weathering, hydrolysis, and microbiological attack. Floating capability.

- **Static Discharge Wires**

Dual bonding wires to EN 1765 allow couplings to be electrically bonded when transferring fuels.



**speck
pumpen**



**SEAFRESH
DESALINATORS**
victron energy
BLUE POWER

